



## PRODUCT DATA SHEET

Date: 05/09/2024

**Spinnaker**  
550 Summit Avenue  
Troy, Oh 45373  
800 543-9452

### DiversiPrint® 60# Bright White \*\* SP924G Permanent \*\* 58# Scored

Facestock: **DiversiPrint® 60# Bright White**

A premium bright white offset offering excellent contrast and ink receptivity, this uncoated sheet is designed to be compatible with most desk top, high-speed laser printers and copiers. Also suitable for ink jet printing.

#### Typical Value

|               |                           |
|---------------|---------------------------|
| Basis Weight: | 60 #/3300 ft <sup>2</sup> |
| Caliper:      | 4.6 mils                  |
| Opacity:      | 92%                       |
| Brightness:   | 98%                       |
| PCW Content:  | 10%                       |
| GSM:          | 202                       |

Adhesive: **SP924G Permanent**

SP924G is an aggressive, acrylic emulsion general-purpose permanent adhesive designed to cut cleanly while yielding excellent adhesion to a wide variety of surfaces, including corrugated and low energy surfaces.

#### Typical Value

|                                  |               |
|----------------------------------|---------------|
| Caliper:                         | .6 mils       |
| Service Temperature:             | -40 to 240 °F |
| Minimum Application Temperature: | 20 °F         |

Release Liner: **58# Scored**

A liner specifically designed to meet the stringent lay flat requirements of digital sheet print media. Combined with the appropriate face stock and adhesive, this liner is suitable for high speed laser production presses and copiers as well as most desktop models. It is also suitable for certain offset applications.

#### Typical Value

|               |                           |
|---------------|---------------------------|
| Basis Weight: | 58 #/3000 ft <sup>2</sup> |
| Caliper:      | 3.8 mils                  |

|                |                |
|----------------|----------------|
| Tensile MD/CD: | 37 / 20 #/inch |
| Tear MD/CD:    | 50 / 65 grams  |
| Opacity:       | 85%            |

**Total Product Caliper:** 9 mils

**Product Basis Weight Per MMSI:** 260.63 #

**Shelf Life:** 12 month(s) when stored at 72° F, 50% RH

*For application recommendations call 877-210-5104*

*For samples or other questions please call your Sales Representative.*

**Important Notice**

These are typical values and should not be considered a specification. Adhesive properties were tested with a film facestock unless denoted with an asterisk(\*).

All trademarks are the property of their respective owners.

All information, recommendations for use, product designations, and descriptive materials about Spinnaker Pressure Sensitive Products, LLC products are believed to be reliable, but the furnishing of such information, recommendations for use, product designations, and descriptive material is for informational purposes only and does not constitute a warranty of any kind by Spinnaker Pressure Sensitive Products, LLC. Because of the variety of possible applications for Spinnaker's products and the continuing development of new applications, all Spinnaker Pressure Sensitive Products, LLC products are sold with the understanding that each purchaser will independently determine the suitability of any product for the purchaser's intended application, converting, and print processes. Spinnaker Pressure Sensitive Products, LLC will review, and may modify the information contained in this document from time to time and customers should ensure they have the most recent information.

Last Revision: 04/15/2024