

PRODUCT DATA SHEET

Date: 04/30/2025

Spinnaker

550 Summit Avenue Troy, Oh 45373 800 543-9452

2mil Matte Silver PET ** SFATM ** 50# liner

Item#: 0048054					
	TRIMLESS PROGRAMS				
	Dist. Ctr	Length	Min. Width	Core	
	Troy, Ohio	5 K	3"	3"	
	Troy, Ohio	2.5 K	3"	3"	
Facestock: 2mil Matte Silver PET	A matte silver polyester film that offers high tear strength, heat resistance, dimensional stability, opacity and chemical resistance. It resists scuff and is appropriate for general durable use. The product shows excellent print characteristics for Flexo and Thermal Transfer printing. This product is not recommended for laser printing.				
	Typical Value				
Basis Weight:	48.6 #/3300 ft ²				
Caliper:	2.1 mils				
Tensile MD/CD:	22700 / 29900 PSI				
Elongation @ Break MD/TD:	160 / 100%				
Opacity:	99%				

Adhesive: SFATM

A clear, general purpose, emulsion acrylic permanent adhesive designed for applications with film facestocks. SFA exhibits excellent ultimate adhesion to polyethylene, polypropylene and glass. Well suited for small, cylindrical labeling and is glove friendly.

	Typical Value	
Coat Weight:	13 #/3300 ft ²	
Coat Weight:	19.24 grams/m ²	
Caliper:	.6 mils	
Adhesion to Stainless Steel, oz. (90° Peel):	27	
Loop Tack, oz.:	33	
Service Temperature:	-40 to +200 °F	
Minimum Application Temperature:	40 °F	
Shear (1000g):	450 minutes	

Release Liner: 50# liner

Basis Weight: Caliper:

Tear MD/CD:

Opacity:

Tensile MD/CD:

A bleached, calendered liner featuring higher tensile and tear properties than the 40# liner, making it an excellent liner for perforating, fan-folding, and edge-punching.

Typical Value 53 #/3000 ft² 3.2 mils

48 / 26 #/inch

45 / 51 grams

74%

Total Product Caliper: 5.9 mils Product Basis Weight Per MMSI: 252.42 #

Shelf Life: 12 month(s) when stored at 72° F, 50% RH

For application recommendations call 877-210-5104 For samples or other questions please call your Sales Representative.

Important Notice

These are typical values and should not be considered a specification. Adhesive properties were tested with a film facestock unless denoted with an asterisk(*).

All trademarks are the property of their respective owners.

All information, recommendations for use, product designations, and descriptive materials about Spinnaker Pressure Sensitive Products, LLC products are believed to be reliable, but the furnishing of such information, recommendations for use, product designations, and descriptive material is for informational purposes only and does not constitute a warranty of any kind by Spinnaker Pressure Sensitive Products, LLC. Because of the variety of possible applications for Spinnaker's products and the continuing development of new applications, all Spinnaker Pressure Sensitive Products, LLC products are sold with the understanding that each purchaser will independently determine the suitability of any product for the purchaser's intended application, converting, and print processes. Spinnaker Pressure Sensitive Products, LLC will review, and may modify the information contained in this document from time to time and customers should ensure they have the most recent information.

Last Revision: 05/04/2020