

PRODUCT DATA SHEET

Date: 04/30/2025

Spinnaker 550 Summit Avenue Troy, Oh 45373 800 543-9452

SafeTE™ NT Red Void Polyester ** VR ** 60# Blue

Item#: 0049946

	TRIMLESS PROGRAMS			
	Dist. Ctr	Length	Min. Width	Core
	Troy, Ohio	2 K	3"	3"
	Troy, Ohio	5 K	3"	3"
Facestock: SafeTE™ NT Red Void Polyester	1.5 mil red non-transferable void polyester, topcoated for superior printability via flexography and thermal transfer printers. Features high strength, tear resistance, dimensional stability and temperature resistance. Print test product and consult with your ink supplier to confirm suitability for your application.			
	Typical Value			
Basis Weight:	35.8 #/3300 ft ²	!		
Caliper:	1.5 mils			
Tensile MD/CD:	241 / 238 MPa	Į.		
Elongation @ Break MD/TD:	199 / 184%			
Gloss:	94.2 / N/A%			
Opacity:	31.9%			

Adhesive: **VR** This is unique removable acrylic that will generate the VOID letter on the film

side but does not make residue on the applied surface. The performance may

vary depending on

the type and finish of the surface, so have prior testing before usage.

Typical Value

Caliper: 1 mils Adhesion to Stainless Steel, oz. (90° Peel): 12 Loop Tack, oz.: 21

Service Temperature: 14 to 176 °F Minimum Application Temperature: 50 °F

Shear (1000g): >10,000 minutes

Release Liner: 60# Blue A 60# blue glassine liner. Excellent for die cutting and stripping. The liner is

coated with a release system designed for label dispensing. Primarily for roll-to-

roll applications where a more demanding liner is needed.

Typical Value

Basis Weight: $60 \#/3000 \text{ ft}^2$ Caliper: 3.5 mils

Total Product Caliper: 6 mils

Product Basis Weight Per MMSI: 214.32 #

Shelf Life: 12 month(s) when stored at 72° F, 50% RH

For application recommendations call 877-210-5104 For samples or other questions please call your Sales Representative.

Important Notice

These are typical values and should not be considered a specification. Adhesive properties were tested with a film facestock unless denoted with an asterisk(*).

All trademarks are the property of their respective owners.

All information, recommendations for use, product designations, and descriptive materials about Spinnaker Pressure Sensitive Products, LLC products are believed to be reliable, but the furnishing of such information, recommendations for use, product designations, and descriptive material is for informational purposes only and does not constitute a warranty of any kind by Spinnaker Pressure Sensitive Products, LLC. Because of the variety of possible applications for Spinnaker's products and the continuing development of new applications, all Spinnaker Pressure Sensitive Products, LLC products are sold with the understanding that each purchaser will independently determine the suitability of any product for the purchaser's intended application, converting, and print processes. Spinnaker Pressure Sensitive Products, LLC will review, and may modify the information contained in this document from time to time and customers should ensure they have the most recent information.

Last Revision: 05/22/2023