

## **PRODUCT DATA SHEET**

Date: 04/30/2025

**Spinnaker** 550 Summit Avenue Troy, Oh 45373 800 543-9452

## 3.5mil TC White Laser Vinyl \*\* RSM-95 \*\* 72# liner

Item#: 0050142

	TRIMLESS PROGRAMS			
	Dist. Ctr	Length	Min. Width	Core
	Troy, Ohio	2.5 K	3"	6"
	Troy, Ohio	5 K	3"	6"
Facestock: 3.5mil TC White Laser Vinyl	Engineered for high-speed and mid-range laser printers*, this laser vinyl has a satin finish and is topcoated to provide excellent toner anchorage. It is appropriate for outdoor usage when properly printed via flexo, monochrome or color laser. Rated at one-year outdoor life. *Due to machine capabilities and setting adjustments, specific printer testing is recommended.			
	Typical Value			
Basis Weight:	85 #/3300 ft <sup>2</sup>			
Caliper:	3.4 mils			
Tensile MD/CD:	3800 / 3330 PS	SI		
Elongation @ Break MD/TD:	119 / 243%			
Opacity:	91%			

Adhesive: **RSM-95** a removable, emulsion acrylic adhesive with good performance for indoor and outdoor use.

	Typical Value
Coat Weight:	12 #/3300 ft <sup>2</sup>
Coat Weight:	$17.76 \text{ grams/m}^2$
Caliper:	.7 mils
Adhesion to Stainless Steel, oz. (90° Peel):	18
Loop Tack, oz.:	32
Service Temperature:	-40 to 180 °F
Minimum Application Temperature:	50 °F
Shear (1000g):	72 minutes

Release Liner: 72# liner

Basis Weight: Caliper:

Tear MD/CD:

Opacity:

Tensile MD/CD:

A bleached, kraft paper used primarily for roll-to-sheet products. The liner is specifically designed to lay flat and is not recommended for roll-to-roll or roll-to-fan-folded applications.

## **Typical Value** 73.6 #/3000 ft<sup>2</sup> 4.6 mils 48 / 28 #/inch

82 / 90 grams

86%

**Total Product Caliper:** 8.7 mils **Product Basis Weight Per MMSI:** 374.65 # **Shelf Life:** 12 month(s) when stored at 72° F, 50% RH For application recommendations call 877-210-5104 For samples or other questions please call your Sales Representative.

## **Important Notice**

These are typical values and should not be considered a specification. Adhesive properties were tested with a film facestock unless denoted with an asterisk(\*).

All trademarks are the property of their respective owners.

All information, recommendations for use, product designations, and descriptive materials about Spinnaker Pressure Sensitive Products, LLC products are believed to be reliable, but the furnishing of such information, recommendations for use, product designations, and descriptive material is for informational purposes only and does not constitute a warranty of any kind by Spinnaker Pressure Sensitive Products, LLC. Because of the variety of possible applications for Spinnaker's products and the continuing development of new applications, all Spinnaker Pressure Sensitive Products, LLC products are sold with the understanding that each purchaser will independently determine the suitability of any product for the purchaser's intended application, converting, and print processes. Spinnaker Pressure Sensitive Products, LLC will review, and may modify the information contained in this document from time to time and customers should ensure they have the most recent information.

Last Revision: 06/14/2024