

## PRODUCT DATA SHEET

Date: 02/24/2023

Spinnaker

550 Summit Avenue Troy, Oh 45373 800 543-9452

## Veero 54# Semi Gloss (2018) \*\* VG-430 \*\* Veero 40# liner (2018)

## Item#: 0048345

TRIMLESS PROGRAMS				
Dist. Ctr	Length	Min. Width	Core	
New York	2.5 K	3"	3"	
New York	5 K	3"	3"	
Atlanta	2.5 K	3"	3"	
Atlanta	5 K	3"	3"	
Chicago	2.5 K	3"	3"	
Chicago	5 K	3"	3"	

Replaces old item# 41439

Facestock: Veero 54# Semi Gloss (2018)	A bright white, semi gloss litho with excellent strength characteristics. The lower basis weight creates an economical sheet, without sacrificing quality. This component is not available for custom constructions
	Typical Value
Basis Weight:	54 #/3300 ft <sup>2</sup>
Caliper:	2.6 mils
Tensile MD/CD:	32 / 15
Gloss:	72%
Tear MD/CD:	30 / 37 grams
Opacity:	85%
Brightness:	91%

 Adhesive: VG-430
 A robust hot-melt, rubber-based adhesive exhibiting excellent adhesion and quick tack to a variety of packaging surfaces over a wide application temperature range. This component is not available for custom constructions.

 Typical Value

 Coat Weight:
 11.5 #/3300 ft<sup>2</sup>

Coat Weight:	11.5 #/3300 ft <sup>2</sup>
Coat Weight:	17.02 grams/m <sup>2</sup>
Caliper:	.35 mils
Adhesion to Stainless Steel, oz. (90° Peel):	58
Loop Tack, oz.:	73

Service Temperature:	-20 to 158 °F
Minimum Application Temperature:	32 °F
Shear (1000g):	553 minutes

Release Liner: Veero 40# liner (2018)	A bleached, calendered liner featuring excellent die cutting and stripping characteristics. Recommended for use in roll-to-roll applications.	
	Typical Value	
Basis Weight:	39 #/3000 ft <sup>2</sup>	
Caliper:	2.4 mils	
Tensile MD/CD:	33 / 16 #/inch	
Tear MD/CD:	26 / 36 grams	
Opacity:	60%	

**Total Product Caliper:** 5.35 mils **Product Basis Weight Per MMSI:** 228.21 # **Shelf Life:** 12 month(s) when stored at 72° F, 50% RH For application recommendations call 877-210-5104 For samples or other questions please call your Sales Representative.

## **Important Notice**

These are typical values and should not be considered a specification. Adhesive properties were tested with a film facestock unless denoted with an asterisk(\*).

All trademarks are the property of their respective owners.

All information, recommendations for use, product designations, and descriptive materials about Spinnaker Pressure Sensitive Products, LLC products are believed to be reliable, but the furnishing of such information, recommendations for use, product designations, and descriptive material is for informational purposes only and does not constitute a warranty of any kind by Spinnaker Pressure Sensitive Products, LLC. Because of the variety of possible applications for Spinnaker's products and the continuing development of new applications, all Spinnaker Pressure Sensitive Products, LLC products are sold with the understanding that each purchaser will independently determine the suitability of any product for the purchaser's intended application, converting, and print processes. Spinnaker Pressure Sensitive Products, LLC will review, and may modify the information contained in this document from time to time and customers should ensure they have the most recent information.

Last Revision: 08/16/2018