

## **PRODUCT DATA SHEET**

Date: 04/26/2024

Spinnaker 550 Summit Avenue Troy, Oh 45373 800 543-9452

8pt C1S Tag

Item#: 0028809

|  | TRIMLESS PROGRAMS   |                       |                  |                  |
|--|---|-----------------------|------------------|------------------|
| Recommended Print Type(s) to Test<br>Flexo | <b>Dist. Ctr</b><br>Troy, Ohio<br>Troy, Ohio  | Length<br>5 K<br>10 K | Min. Width 3" 4" | Core<br>3"<br>3" |
| Facestock: 8pt C1S Tag                     | A C1S tag stock designed to be used in applications requiring high strength and stiffness, such as hang tags and shelf talkers. |                       |                  |                  |
|  | Typical Value   |                       |                  |                  |
| Basis Weight:                              | 108 #/3300 ft <sup>2</sup>  |                       |                  |                  |
| Caliper:                                   | 8.7 mils  |                       |                  |                  |
| Tensile MD/CD:                             | 80 / 40   |                       |                  |                  |
| Gloss:                                     | 51%   |                       |                  |                  |
| Tear MD/CD:                                | 135 / 145 grams   |                       |                  |                  |
| Opacity:                                   | 96.9%   |                       |                  |                  |
| Parker Print:                              | 1.1 microns   |                       |                  |                  |
| Brightness:                                | 91.5%   |                       |                  |                  |

**Total Product Caliper:** 8.7 mils

**Shelf Life:** 12 month(s) when stored at 72° F, 50% RH

**Important Notice** 

For application recommendations call 877-210-5104 For samples or other questions please call your Sales Representative. **Product Basis Weight Per MMSI: 227.37 #** 

These are typical values and should not be considered a specification. Adhesive properties were tested with a film facestock unless denoted with an asterisk(\*).

All trademarks are the property of their respective owners.

All information, recommendations for use, product designations, and descriptive materials about Spinnaker Pressure Sensitive Products, LLC products are believed to be reliable, but the furnishing of such information, recommendations for use, product designations, and descriptive material is for informational purposes only and does not constitute a warranty of any kind by Spinnaker Pressure Sensitive Products, LLC. Because of the variety of possible applications for Spinnaker's products and the continuing development of new applications, all Spinnaker Pressure Sensitive Products, LLC products are sold with the understanding that each purchaser will independently determine the suitability of any product for the purchaser's intended application, converting, and print processes. Spinnaker Pressure Sensitive Products, LLC will review, and may modify the information contained in this document from time to time and customers should ensure they have the most recent information.

Last Revision: 03/08/2023