

PRODUCT DATA SHEET

Date: 04/26/2024

Spinnaker

550 Summit Avenue Troy, Oh 45373 800 543-9452

Satin Matte Ink Jet Paper ** CLD-10 ** 40# liner

Item#: 0048482

Troy, Ohio2.5 K3"Troy, Ohio5 K3"Troy, Ohio10 K4"Facestock:Satin Matte Ink Jet PaperThis matte paper is designed to be compatible with most of roll-to-roll, and wide-format ink jet printers. This sheet di good photo images, color graphics, and text. It has good fastness and wet-rub characteristics.Basis Weight:61 #/3300 ft²Caliper:3.6 milsTensile MD/CD:32 / 16Gloss:23%Tear MD/CD:71 / 70 gramsOpacity:95%Sheffield Smoothness:28 SFUParker Print:2.4 microns	TRIMLESS PROGRAMS				
Troy, Ohio5 K3" Troy, Ohio10 K4"Facestock:Satin Matte Ink Jet PaperThis matte paper is designed to be compatible with most or oll-to-roll, and wide-format ink jet printers. This sheet d good photo images, color graphics, and text. It has good fastness and wet-rub characteristics.Basis Weight:61 #/3300 ft²Caliper:3.6 milsTensile MD/CD:32 / 16Gloss:23%Tear MD/CD:71 / 70 gramsOpacity:95%Sheffield Smoothness:28 SFUParker Print:2.4 microns	Core	Min. Width	Length	Dist. Ctr	
Troy, Ohio10 K4"Facestock:Satin Matte Ink Jet PaperThis matte paper is designed to be compatible with most or roll-to-roll, and wide-format ink jet printers. This sheet d good photo images, color graphics, and text. It has good fastness and wet-rub characteristics.Basis Weight:61 #/3300 ft²Caliper:3.6 milsTensile MD/CD:32 / 16Gloss:23%Tear MD/CD:71 / 70 gramsOpacity:95%Sheffield Smoothness:28 SFUParker Print:2.4 microns	3"	3"	2.5 K	Troy, Ohio	
Facestock: Satin Matte Ink Jet PaperThis matte paper is designed to be compatible with most or roll-to-roll, and wide-format ink jet printers. This sheet d good photo images, color graphics, and text. It has good fastness and wet-rub characteristics.Basis Weight:61 #/3300 ft²Caliper:3.6 milsTensile MD/CD:32 / 16Gloss:23%Tear MD/CD:71 / 70 gramsOpacity:95%Sheffield Smoothness:28 SFUParker Print:2.4 microns	3"	3"	5 K	Troy, Ohio	
roll-to-roll, and wide-format ink jet printers. This sheet d good photo images, color graphics, and text. It has good fastness and wet-rub characteristics. Typical Value Basis Weight: 61 #/3300 ft ² Caliper: 3.6 mils Tensile MD/CD: 32 / 16 Gloss: 23% Tear MD/CD: 71 / 70 grams Opacity: 95% Sheffield Smoothness: 28 SFU Parker Print: 2.4 microns	3"	4"	10 K	Troy, Ohio	
Typical ValueBasis Weight:61 #/3300 ft²Caliper:3.6 milsTensile MD/CD:32 / 16Gloss:23%Tear MD/CD:71 / 70 gramsOpacity:95%Sheffield Smoothness:28 SFUParker Print:2.4 microns	t delivers	nk jet printers. This sh	wide-format in	cestock: Satin Matte Ink Jet Paper	
Basis Weight:61 #/3300 ft²Caliper:3.6 milsTensile MD/CD:32 / 16Gloss:23%Tear MD/CD:71 / 70 gramsOpacity:95%Sheffield Smoothness:28 SFUParker Print:2.4 microns					
Caliper:3.6 milsTensile MD/CD:32 / 16Gloss:23%Tear MD/CD:71 / 70 gramsOpacity:95%Sheffield Smoothness:28 SFUParker Print:2.4 microns				Typical Value	
Tensile MD/CD:32 / 16Gloss:23%Tear MD/CD:71 / 70 gramsOpacity:95%Sheffield Smoothness:28 SFUParker Print:2.4 microns				61 #/3300 ft ²	sis Weight:
Gloss:23%Tear MD/CD:71 / 70 gramsOpacity:95%Sheffield Smoothness:28 SFUParker Print:2.4 microns				3.6 mils	iper:
Tear MD/CD:71 / 70 gramsOpacity:95%Sheffield Smoothness:28 SFUParker Print:2.4 microns				32 / 16	nsile MD/CD:
Opacity:95%Sheffield Smoothness:28 SFUParker Print:2.4 microns				23%	DSS:
Sheffield Smoothness:28 SFUParker Print:2.4 microns				71 / 70 grams	ar MD/CD:
Parker Print:2.4 microns				95%	acity:
				28 SFU	effield Smoothness:
				2.4 microns	ker Print:
Brightness: 92%				92%	ghtness:

Adhesive: CLD-10

An economical cold temperature hot melt adhesive for a broad range of cold temperature applications needing high initial tack with excellent die cutting and stripping properties. The adhesive performs well when there is light moisture present during application.

Typical Value

	• •
Coat Weight:	12 #/3300 ft ²
Coat Weight:	17.76 grams/m ²
Caliper:	.5 mils
Adhesion to Stainless Steel, oz. (90° Peel):	30
Loop Tack, oz.:	52
Service Temperature:	-50 to 145 °F
Minimum Application Temperature:	10 °F
Shear (1000g):	60 minutes

Release Liner: 40# liner

A bleached, calendered liner featuring excellent die cutting and stripping characteristics. Recommended for use in roll-to-roll applications.

Basis Weight: Caliper: Tensile MD/CD: Tear MD/CD: Opacity: **Typical Value** 41 #/3000 ft² 2.5 mils 34 / 21 #/inch 34 / 36 grams 69 max%

Total Product Caliper: 6.6 mils **Product Basis Weight Per MMSI:** 248.63 # **Shelf Life:** 12 month(s) when stored at 72° F, 50% RH

For application recommendations call 877-210-5104 For samples or other questions please call your Sales Representative.

Important Notice

These are typical values and should not be considered a specification. Adhesive properties were tested with a film facestock unless denoted with an asterisk(*).

All trademarks are the property of their respective owners.

All information, recommendations for use, product designations, and descriptive materials about Spinnaker Pressure Sensitive Products, LLC products are believed to be reliable, but the furnishing of such information, recommendations for use, product designations, and descriptive material is for informational purposes only and does not constitute a warranty of any kind by Spinnaker Pressure Sensitive Products, LLC. Because of the variety of possible applications for Spinnaker's products and the continuing development of new applications, all Spinnaker Pressure Sensitive Products, LLC products are sold with the understanding that each purchaser will independently determine the suitability of any product for the purchaser's intended application, converting, and print processes. Spinnaker Pressure Sensitive Products, LLC will review, and may modify the information contained in this document from time to time and customers should ensure they have the most recent information.

Last Revision: 08/31/2023